Name	Organoid [®] MOUNTAIN MEADOW on flax backing
Article number Address	WSPBRG0075FVPRW ORGANOID GmbH Nesselgarten 422 / Top 5 A-6500 Fließ Austria
Name Description Applications	Organoid® MOUNTAIN MEADOW on flax backing Natural plant material in full coverage on natural non-woven flax backing produced climate neutral in Tyrol As wallpaper As décor, like veneer on backing boards
Plant material Density	Approx. 6 edelweiss/m ² , approx. 5 daisies/m ² and colourful flower petals on regional, hand- cut Alpine hay from the Tyrolean Alps Premium density, full coverage
Size Thickness Weight	Rolled goods, width 1 360 mm 1.0 mm 550 g/m²
Hardly inflammable Food-safety	C-s1, d0 in accordance with EN ISO 13501-01 Binding agent safe for usage in contact with food in accordance with EU-regulation 1935/2004
Material Properties	Non-woven blend of flax and viscose Unbleached and breathable from renewable materials Contains 65% flax and 35% viscose Certified OEKO-TEX 100 Tensile strength in accordance with ISO9073-3: MD N/5cm >100 CD N/5cm >70
Cut Edges How to install	 Use scissors, a cutter or a plotter Allow for imperfections 1-2 mm around the edges <u>As wallpaper:</u> Wall-pasting technique: Apply glue directly on the wall, apply wallpaper vertically and press on using a rubber roller Double cut: Each panel overlaps with the one next to it (approx. 2 cm) Free match: The naturally scattered materials do not require matching patterns between panels
	Article number Address Name Description Applications Plant material Density Size Thickness Weight Hardly inflammable Food-safety Material Properties

	 <u>As décor:</u> Process with normal wood-working machinery Glue (e.g. white glue) is applied onto the wooden materials, as the fleece absorbs moisture and glue stains may appear on the front if glue is applied to the fleece Cover the natural surface with the enclosed separating paper Guidelines: Max. pressing temperature. 60°C Max. pressure 1 kg/cm² Glue application: approx. 100 g/m² Pressing time: approx. 15 minutes
Glue recommendations	As wallpaper: Glutolin ECC extra clear As décor, like veneer on backing boards: White glue
Pay attention to	Surface must be clean, dry, weight-bearing, evenly absorbent, smooth, dust-free and neutral in colour. Recently plastered walls must be fully dried. Highly absorbent walls must be prepared with a suitable base. For sensitive wood-working applications, use a counter-balance (enclosed on request). Symmetrical construction is recommended, which means using the same surface on the front and back side.
	 Acclimatisation of Organoid natural surfaces: Bring product to room temperature before unpacking Store product protected from light, at about 20°C and 30-60 % relative humidity.
Processing guidelines available at:	 Storage: Rolled goods: hanging system (e.g. paternoster) Single panels: horizontal position (e.g. drawer system) www.organoids.com/en/processing