Product Producer	Name Article number Address	Organoid® SKELETTBLATTLA on golden paper SKL0000010GTARW ORGANOID TECHNOLOGIES GMBH Nesselgarten 422 / Top 5 A-6500 Fließ Österreich
Description and applications	Name Description	Organoid <sup>®</sup> SKELETTBLATTLA on golden paper Natural plant material in full coverage on
		golden paper produced climate neutral in Tyrol
	Applications	As paper As a compound in wood-working
Plant material and density	Plant material	Skeletonised rubber leaves, approx. 200/m <sup>2</sup>
	Density	Premium, full coverage
Size and weight	Size Thickness Weight	Rolled goods, width 1 360 mm 0.2 mm 230 g/m²
Product requirements	Food-safety	Binding agent safe for usage in contact with food in accordance with EU-regulation 1935/2004
Backing material	Material Properties	Golden paper Shimmering
Technical implementation	Cut	Use scissors, a cutter or a plotter
	Edges	Allow for imperfections 1-2 mm around the edges
	How to install	<u>As a compound in wood-working</u> -Process with normal wood-working machinery -Glue (e.g. white glue) is applied onto the wooden materials, as the fleece absorbs moisture and glue stains may appear on the
		front if glue is applied to the fleece -Cover the natural surface with the enclosed separating paper -Guidelines:
		Max. pressing temperature. 60°C Max. pressure 1 kg/cm <sup>2</sup> Glue application: approx. 100 g/m <sup>2</sup> Pressing time: approx. 15 minutes
		Pre-trials and tests are recommended

Glue recommendations	As a compound in wood-working: White glue
Pay attention to	Surface must be clean, dry, weight-bearing, evenly absorbent, smooth, dust-free and neutral in colour. Recently plastered walls must be fully dried. Highly absorbent walls must be prepared with a suitable base.
	For sensitive wood-working applications, use a counter-balance (enclosed on request). Symmetrical construction is recommended, which means using the same surface on the front and back side.
	<ul> <li>Acclimatisation of Organoid natural surfaces:</li> <li>Bring product to room temperature before unpacking</li> <li>Store product protected from light, at about 20°C and 30-60 % relative humidity.</li> <li>Storage: <ul> <li>Rolled goods: hanging system (e.g. paternoster)</li> <li>Single panels: horizontal position (e.g. drawer system)</li> </ul> </li> </ul>
Processing guidelines	https://organoid.corestad.com/verarbeitung/
available at:	(= current link)